

PRODUCT DESCRIPTION:

DUREX DRYWALL PRIMER is an interior latex primer formulated for application to drywall surfaces.

USES:

DUREX DRYWALL PRIMER is used as a primer for drywall substrates prior to the application of paint.

ADVANTAGES:

- breathable, allows water vapour within the wall system to evaporate
- excellent adhesion to substrate
- superior hiding power

LIMITATIONS:

DUREX DRYWALL PRIMER is not recommended for use:

- over substrates other than drywall
- over previously treated surfaces without proper preparation

- surfaces where oils and other contaminants are present
- when ambient, surface and material temperatures are below 5°C (41°F) during application and curing period
- for exterior applications

APPLICATION:

DO NOT SUBSTITUTE NOR COMPENSATE **DUREX DRYWALL PRIMER** WITH WATER OR OTHER ADDITIVES.

Drywall surfaces must be clean and sound, free of weak and powdery surfaces, dust, dirt, oil, grease and other deleterious materials detrimental to a positive bond.

Check with **Durabond Products Limited** for questionable surfaces.

Thoroughly stir **DUREX DRYWALL PRIMER** in its own pail before each use. Discard all frozen materials, materials which have formed solid lumps at the bottom of the container and materials which do not appear to be of a homogeneous viscosity.

TECHNICAL DATA

Physical Properties:

Product type:	Water based latex emulsion
Appearance:	White milky dense liquid
Viscosity	1500 to 2000 cps
Ph level:	6.0 to 6.5
Toxicity:	Non-toxic
Coverage:	4.08 to 8.16 m ² /L (200 to 400 ft ² /gal.)
Finish time:	Flat
Drying time:	20 to 30 minutes @ 21°C (depending on porosity of substrate)
Substrate requirement:	Clean, solid taped & sanded drywall

09910

DECORATIVE FINISHES
ACRYLIC GYPSUM BOARD PRIMER

Apply **DUREX DRYWALL PRIMER** evenly by roller or brush. Avoid dripping and applying too much primer in any one pass.

CLEAN UP:

Clean all tools promptly after EACH use with clean water. Do not allow primer to dry on tools.

STORAGE:

Store **DUREX DRYWALL PRIMER** in a dry, vented, waterproof location, stacked off the ground with ambient temperatures above 5°C (41°F). Keep materials dry, protected from rapid temperature changes, dampness and moisture and away from direct sunlight.

KEEP FROM FREEZING.

PACKAGING:

DUREX DRYWALL PRIMER is packaged in 18.9 litre pails, in white colour. Custom colours are available upon request for a slight additional charge.

COVERAGE:

One pail of **DUREX DRYWALL PRIMER** will cover approximately 186 m² (2,000 ft²).

WARRANTY:

Durabond Products Limited fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case **Durabond's** responsibility shall not exceed either the refund of the purchase price, or the replacement of the purchased product.

TECHNICAL SERVICES:

Technical assistance for unique applications and design is available upon request from **Durabond Products Limited**.

DURabond

Manufacturers and Distributors of High Quality Construction Products

55 Underwriters Road, Toronto, Ontario M1R 3B4

Tel: (416) 759-4474 Toll Free: 1-877-DURABOND (387-2266) Fax: (416) 759-4470

Email: info@durabond.com Website: www.durabond.com