

PRODUCT DESCRIPTION:

DUREX JOINT COMPOUND is a high quality, asbestos-free, ready mixed all purpose compound for filling joints and holes in drywall construction.

ADVANTAGES:

- lightweight
- ready to use
- excellent adhesion and workability
- very little shrinkage; thus minimum cracking
- easier sanding

LIMITATIONS:

DUREX JOINT COMPOUND is for interior applications only. Ambient, surface and material temperatures must be above 13°C. (55°F) during application and for minimum 48 hours after application.

MIXING PROCEDURE:

Mix compound in original container prior to use.

DO NOT SUBSTITUTE NOR COMPENSATE **DUREX**

JOINT COMPOUND WITH WATER OR OTHER ADDITIVES.

Discard all materials which have begun to harden.

APPLICATION:

Drywall surfaces must be clean and sound, free of weak and powdery surfaces, dust, dirt, oil, grease and any other deleterious materials detrimental to a positive bond.

Deteriorating, weak, powdering sections of drywall must be replaced.

Check with **Durabond Products Limited** for questionable surfaces.

Thinning the compound is not recommended.

However if job conditions require a thinner compound, add potable water, up to maximum 1 quart per gallon of compound and mix. Consult **Durabond Products Limited** where such thinning may be required.

Allow compound to dry thoroughly between coats.

TECHNICAL DATA

Physical Properties:

Product type:	Ready mixed, non cementitious calcium carbonate
Appearance:	Thick white paste
Toxicity:	Non-toxic
Pot life:	24 hrs. after opening of box

Performance Characteristics:

Mixing ratio:	No mixing required ready mixed. Small amounts of water can be added to desired consistency.
Coverage:	Coverage will vary according to texture method of application.
Average consumption:	1 box per 10.2 m ² (500 ft ²) drywall taped
Substrate requirement:	Clean solid drywall

09202

PLASTER ACCESSORIES
GYPSUM BOARD COMPOUND

CLEAN UP:

Clean all tools promptly after each use with water. Do not allow mixes to dry on tools.

STORAGE:

Store **DUREX JOINT COMPOUND** in a dry, vented, waterproof location, stacked off the ground with ambient temperatures above 13°C (55°F). Keep materials dry, protected from rapid temperature changes, dampness and moisture and away from direct sunlight.

KEEP FROM FREEZING.

PACKAGING:

DUREX JOINT COMPOUND is readily available in 20 kg pails, 17 kg boxes and 4 litre pails. It is available in white, light grey and grey colours.

WARRANTY:

Durabond Products Limited fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case **Durabond's** responsibility shall not exceed either the refund of the purchase price, or the replacement of the purchased product.

TECHNICAL SERVICES:

Technical assistance for unique applications and design is available from upon request from **Durabond Products Limited**.

DURabond

Manufacturers and Distributors of High Quality Construction Products

55 Underwriters Road, Toronto, Ontario M1R 3B4

Tel: (416) 759-4474 Toll Free: 1-877-DURABOND (387-2266) Fax: (416) 759-4470

Email: info@durabond.com Website: www.durabond.com