

### PRODUCT DESCRIPTION:

**DUREX MONOCAPA** is a polymer modified, Portland cement-based plaster, which has been formulated with numerous ideal features to provide a versatile, hard, strong, durable, fire and weather resistant surfacing material. **DUREX MONOCAPA** can be used in a variety of exterior/interior applications both on vertical and horizontal planes and in the hands of a skilled tradesman can be worked into patterns and textures flat of curvilinear surfaces.

### USES:

**DUREX MONOCAPA** can be used as a base coat in the **DUREX Lite Coat** and **DUREX Stucco Lite Systems**, over new or existing substrates such as masonry, concrete, concrete block, brick, or other cementitious renderings.

### ADVANTAGES:

**DUREX MONOCAPA** is a user friendly premixed plaster mix which requires only the addition of potable water, It provides the following features:

- Excellent workability
- Maximum crack control
- Maximum quality control
- Minimum mixing time
- Low cost
- Consistency and ease of duplication of mixes
- Rated non-combustible
- Rot and fungus resistant

### LIMITATIONS:

Mix **DUREX MONOCAPA** only with potable water. Ambient, surface and material temperatures must be above 5°C (41°F) during application and curing period.

### MIXING PROCEDURE:

DO NOT SUBSTITUTE NOR COMPENSATE **DUREX MONOCAPA** WITH OTHER ADDITIVES.

Discard all materials which have begun to harden. Mix **DUREX MONOCAPA** with potable water in the following proportions:

<b>DUREX MONOCAPA</b>	1 bag
Potable water	4-5 litres

### APPLICATION:

Trowel apply the **DUREX MONOCAPA**, applying sufficient force to ensure full bond with the substrate and that all voids in the substrate are filled. Use a straight edge tool to darby the surface and bring it to a straight, even and true surface. Total thickness of the **DUREX MONOCAPA** should not exceed 12.7 mm (1/2"). Total thickness per lift shall not exceed 6 mm (1/4").

### CLEAN-UP:

Clean all tools promptly after each use with clean, warm water. Do not allow mixes to dry on tools.

### STORAGE:

Store **DUREX MONOCAPA** in a dry, vented, waterproof location, stacked off the ground with ambient temperatures above 5°C (41°F). Keep materials dry, protected from rapid temperature changes, dampness and moisture and away from direct sunlight.

### PACKAGING:

**DUREX MONOCAPA** is available in 22.7 kg bags.

### COVERAGE:

Each bag provides 1m<sup>2</sup> (10.8 ft<sup>2</sup>) coverage at 10-12 mm thickness.

### WARRANTY:

**Durabond Products Limited** fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case **Durabond's** responsibility shall not exceed either the refund purchase price, or the replacement of the purchased product.

### TECHNICAL SERVICES:

Technical assistance for unique applications and design is available upon request from **Durabond Products Limited**.

---

**DURabond**

Manufacturers and Distributors of High Quality Construction Products

55 Underwriters Road, Toronto, Ontario M1R 3B4

Tel: (416) 759-4474 Toll Free: 1-877-DURABOND (387-2266) Fax: (416) 759-4470

Email: [info@durabond.com](mailto:info@durabond.com) Website: [www.durabond.com](http://www.durabond.com)

**F-31**