

PRODUCT DESCRIPTION:

DUREX STUCCO BINDER is a water based, 100% acrylic polymer cement additive. **DUREX STUCCO BINDER** has been specially formulated to provide maximum adhesion and ideal application properties when mixed with **Durex Uniplast**.

USES:

DUREX STUCCO BINDER when mixed with **Durex Uniplast** is used as:

- scratch and base coat for the **Durex “Lite Coat”** system
- concrete wall patching for shallow repairs, maximum 6.4 mm (1/4") deep
- cementitious parge coat for masonry and concrete walls

ADVANTAGES:

DUREX STUCCO BINDER is formulated to provide:

- consistent job site quality control of mixes
- better controlled workability features of mixes
- low moisture absorption rate of the mixtures

- reduced shrinkage and cracking of the cementitious mixtures
- higher compressive and flexural strength than sand/cement plaster mixes
- better and more complete hydration of cement

LIMITATIONS:

DUREX STUCCO BINDER is not recommended for use:

- with mixes on horizontal wearing surfaces
- when ambient, surface and material temperatures are below 5°C (41°F) during application and curing period

CLEAN-UP:

Clean all tools promptly after use with clean water. Do not allow mixes to dry on tools.

STORAGE:

Store **DUREX STUCCO BINDER** in a dry, vented, waterproof location, stacked off the ground with ambient temperatures above 5°C (41°F). Keep materials dry, protected from rapid temperature

TECHNICAL DATA

Physical Properties:

Product type:	Water based acrylic emulsion
Appearance:	White milky liquid
Viscosity:	50-90 cps
Ph level:	9.0-9.5
Toxicity:	Non-toxic
Mix open time:	45 minutes

Performance Characteristics:

Note: (For performance characteristics see **Durex Lite Coat** data sheet in **Group G**. See also **Durex Uniplast** data sheet in **Group F**.)

03051

ADMIXTURES & ACCESSORIES
CEMENT BONDING AGENTS

changes, dampness and moisture and away from direct sunlight.

KEEP FROM FREEZING.

PACKAGING:

DUREX STUCCO BINDER is readily available in 4 litre containers, 18.9 litre pails and 45 gallon (205 litres) drums.

WARRANTY:

Durabond Products Limited fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case **Durabond's** responsibility shall not exceed either the refund of the purchase price, or the replacement of the purchased product.

TECHNICAL SERVICES:

Technical assistance for unique applications and design is available upon request from **Durabond Products Limited**.

DURabond

Manufacturers and Distributors of High Quality Construction Products

55 Underwriters Road, Toronto, Ontario M1R 3B4

Tel: (416) 759-4474 Toll Free: 1-877-DURABOND (387-2266) Fax: (416) 759-4470

Email: info@durabond.com Website: www.durabond.com