

### PRODUCT DESCRIPTION:

**DUREX TEXTURE SPRAY** is a lightweight economical texturing plaster finish for ceilings.

### USES:

To provide an aesthetically pleasing stipple finish over primed drywall and gypsum plaster ceilings and other primed substrates. Primarily intended for residential construction.

### ADVANTAGES:

- versatile texturing product
- economical
- only add potable water for mixing
- excellent adhesion over a wide number of substrates

### LIMITATIONS:

**DUREX TEXTURE SPRAY** is not recommended for use:

- in interior high humidity areas nor for exterior applications

- when ambient, surface and material temperatures are below 5°C (41°F)
- for wall applications

### MIXING PROCEDURE:

DO NOT SUBSTITUTE NOR COMPENSATE **DUREX TEXTURE SPRAY** WITH OTHER ADDITIVES.

Discard all materials which have begun to harden.

Mix **DUREX TEXTURE SPRAY** with clean potable water. Mix 1 bag (40 lbs) of **DUREX TEXTURE SPRAY** with 18 litres (4 gal.) of water.

Using clean equipment, sift contents of bag into the water; mix until a creamy lump-free consistency is achieved. Do not overmix. Let stand for 10 to 15 minutes. Retemper and use.

### APPLICATION:

Substrate must be dry, solid and sound, free of weak and powdery surfaces, oil, grease, releasing agents and other deleterious materials detrimental to a positive bond.

### TECHNICAL DATA

#### Physical Properties:

<b>Product type:</b>	Perlite/calcium carbonate base texturing product
<b>Appearance:</b>	White fine powder aggregates
<b>Toxicity:</b>	Classified as dust
<b>Bulk Density:</b>	1290 kg/m <sup>3</sup> (80 lb/ft <sup>3</sup> )
<b>Pot life:</b>	24 hrs. to 36 hrs.
<b>Mixing ratio:</b>	1 bag <b>DUREX TEXTURE SPRAY</b> 40 lbs 18 litres (4 gal) water
<b>Coverage:</b>	Coverage will vary according to texture selected and texturing method used.
<b>Average coverage:</b>	16.5 to 27.8 m <sup>2</sup> (180 to 300 ft <sup>2</sup> ) per bag
<b>Substrate required:</b>	<b>Durex Ceiling Coat</b> (cured), primed drywall, primed plaster surfaces.

09215

DECORATIVE FINISHES  
INTERIOR CEILING TEXTURED FINISH

Check with **Durabond Products Limited** for questionable surfaces.

For drywall and gypsum plaster ceilings prime all surfaces to be textured with **Durex Drywall Primer** and allow to dry for a minimum of 24 hours before applying **DUREX TEXTURE SPRAY**.

For concrete ceilings treat all surfaces with **Durex Ceiling Coat** and allow to cure for a minimum of 24 hours before applying **DUREX TEXTURE SPRAY**.

Heavier textures can be achieved by applying **DUREX TEXTURE SPRAY** in a series of two (2) or more coats, allowing each coat to dry between coats for a minimum of two hours. Do not apply more than three (3) coats in any one day period.

#### **CLEAN-UP:**

Clean all tools promptly after each use with clean water. Do not allow mixes to dry on tools.

#### **STORAGE:**

Store **DUREX TEXTURE SPRAY** in a dry, vented, waterproof location, stacked off the ground with ambient temperatures above 5°C (41°F). Keep materials dry, protected from rapid temperature changes, dampness and moisture and away from direct sunlight. KEEP FROM FREEZING.

#### **PACKAGING:**

**DUREX TEXTURE SPRAY** is available in 18.1 kg (40 lb) bags and in 11.3 kg (25 lb) bags.

#### **COVERAGE:**

Depending on the texture desired an 18.1 kg (40 lb) bag of the **DUREX TEXTURE SPRAY** can cover from 16.5 to 27.8 m<sup>2</sup> (180 to 300 ft<sup>2</sup>) of surface.

#### **WARRANTY:**

**Durabond Products Limited** fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case **Durabond's** responsibility shall not exceed either the refund of the purchase price, or the replacement of the purchased product.

#### **TECHNICAL SERVICES:**

Technical assistance for unique applications and design is available upon request from **Durabond Products Limited**.

---

# **DURabond**

Manufacturers and Distributors of High Quality Construction Products

55 Underwriters Road, Toronto, Ontario M1R 3B4

Tel: (416) 759-4474 Toll Free: 1-877-DURABOND (387-2266) Fax: (416) 759-4470

Email: [info@durabond.com](mailto:info@durabond.com) Website: [www.durabond.com](http://www.durabond.com)

**F-5**